

Noise Reduction Rating **18** DECIBELS
(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGH NUMBERS DENOTE GREATER EFFECTIVENESS.)

MSA SORDIN AB – SWEDEN #75302

Federal law prohibits removal of this label prior to purchase.  LABEL REQUIRED BY US E.P.A. REGULATION 40 CFR Part 211, Subpart B

ATTENUATION DATA – Supreme Pro #75302

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean (dB)	11,1	16,5	23,1	25,0	29,5	33,9	35,5	38,3	38,7	18
Standard deviation (dB)	2,6	3,0	3,2	2,8	4,1	3,1	3,6	4,0	3,2	

Noise Reduction Rating **21** DECIBELS
(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGH NUMBERS DENOTE GREATER EFFECTIVENESS.)

MSA SORDIN AB – SWEDEN #75318

Federal law prohibits removal of this label prior to purchase.  LABEL REQUIRED BY US E.P.A. REGULATION 40 CFR Part 211, Subpart B

ATTENUATION DATA – Supreme Pro WW #75318

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean (dB)	15,6	19,0	26,4	27,0	27,8	35,1	41,5	43,0	43,8	21
Standard deviation (dB)	3,6	2,2	2,0	2,4	2,3	2,0	4,0	2,1	2,7	

Noise Reduction Rating **19** DECIBELS
(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGH NUMBERS DENOTE GREATER EFFECTIVENESS.)

MSA SORDIN AB – SWEDEN #76302

Federal law prohibits removal of this label prior to purchase.  LABEL REQUIRED BY US E.P.A. REGULATION 40 CFR Part 211, Subpart B

ATTENUATION DATA – Supreme Pro #76302

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean (dB)	14,7	17,2	24,3	23,5	27,3	34,7	38,5	41,5	41,7	19
Standard deviation (dB)	3,7	2,1	2,9	2,5	2,6	2,8	3,7	1,6	2,5	