

AVENGER

military & law enforcement tactical headset solution

The Avenger MIL-Spec communications headset with innovative MSA Sordin electronics provides total situational awareness. The level dependent function protects you from hazardous noise at the same time allows the wearer to hear surrounding sounds. The ambient sound is detected by two microphones mounted on the outside of each cup and reproduced through speakers inside the ear muffs. With two sets of speakers in each ear cup, one for level dependent feature and one for radio communication, it ensures the headset's always has live communication with two-way radio, even if the batteries for the 'active' are completely dead.

The Avenger MIL-Spec, level dependent headsets are equipped with a noise cancelling boom microphone and a heavy duty down lead. The headset provides high noise reduction yet with a slim design.

Available in Headband, Neckband and ARC helmet attachment, Green or black cups and microphone on right or left side for left/right handed shooters.



AVENGER

Features

- Available with Green or Black cups and as headband, neckband or ARC helmet adaptor
- Microphone mounted as standard on the left cup for right handed shooters. Available on right side cup for left handed shooters.
- Equipped with two loudspeakers in each cup, one for level dependent function and one for radio communications
- Waterproof Internal electronics, battery compartment and microphones
- Noise cancelling boom microphone with crystal clear communication
- Two independent external microphones powered by two AAA batteries allows situational awareness in high risk environments
- Low battery warning and save functions (~600 hrs of battery life)



Optional:
Gel earseals
 Product Code: 60092



Additional option:
**Avenger Singlecom
 Tactical Radio PTT
 Adaptor**



Headband & ARC Helmet Mount

Frequency (Hz)	125	250	500	1000	2000	3150	4000	63000	8000	NRR
Mean (dB)	11.1	16.5	23.1	25	29.5	33.9	35.5	38.3	38.7	18
Standard deviation (dB)	2.6	3	3.2	2.8	4.1	3.1	3.6	4.0	3.2	

Neckband

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean (dB)	14.7	17.2	24.3	23.5	27.3	34.7	38.5	41.5	41.7	19
Standard deviation (dB)	3.7	2.1	2.9	2.5	2.6	2.8	3.7	1.5	2.5	



SRS Tactical USA
 Tel: +1 352-795-4848
www.srstactical.com

SRS Tactical Canada
 Tel: +1 403-453-0040
www.srstactical.ca